### Safety Data Sheet

according to Regulation (EU) No. 2015/830

Date of issue: Revision date: 17/06/2015 Supersedes: 11/10/2013 Version: 3.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** 

Product form : Mixture Product name : Tempo Spray

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Temporary adhesive

### Uses advised against

No additional information available

### Details of the supplier of the safety data sheet

JUSTON Aîné Fils Z.A. 60-70 Rue Léon Gaumon 26902 VALENCE Cédex 9 - FRANCE T+33 4 75 43 00 32 - F+33 4 75 55 93 72 Jean-Pierre@Juston.fr

#### 1.4. **Emergency telephone number**

Country	Organisation/Company	Address	Emergency number
UNITED KINGDOM	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)

### **SECTION 2: Hazards identification**

### Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222:H229 Skin Irrit. 2 H315 Eye Irrit. 2 H319 STOT SE 3 H336 Aquatic Chronic 2 H411

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects

: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

### **Label elements**

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

GHS09

Signal word (CLP)

Hazardous ingredients : Naphtha (petroleum) hydrotreated light, butanone

H222 - Extremely flammable aerosol Hazard statements (CLP)

H229 - Pressurised container: May burst if heated

H315 - Causes skin irritation H319 - Causes serious eye irritation H336 - May cause drowsiness or dizziness H411 - Toxic to aquatic life with long lasting effects

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Precautionary statements (CLP) smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P261 - Avoid breathing spray

17/06/2015 1/8 EN (English)

### Safety Data Sheet

according to Regulation (EU) No. 2015/830

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

**EUH-statements** EUH208 - Contains zinc bis(dibutyldithiocarbamate)(136-23-2). May produce an allergic

reaction

#### 2.3. Other hazards

Other hazards not contributing to the

classification

: None, to our knowledge.

## **SECTION 3: Composition/information on ingredients**

Not applicable

#### **Mixture** 3.2.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Propellant gas			
dimethyl ether substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (GB)	(CAS No) 115-10-6 (EC no) 204-065-8 (EC index no) 603-019-00-8	50 - 70	Flam. Gas 1, H220 Press. Gas
Butane substance with national workplace exposure limit(s) (GB)	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0	< 30	Flam. Gas 1, H220 Press. Gas
Propelled liquid			
Naphtha (petroleum) hydrotreated light	(CAS No) 64742-49-0 (EC no) 265-151-9 (EC index no) 649-328-00-1	> 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
butanone	(CAS No) 78-93-3 (EC no) 201-159-0 (EC index no) 606-002-00-3	1 - 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Ethanol	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319
zinc bis(dibutyldithiocarbamate)	(CAS No) 136-23-2 (EC no) 205-232-8 (EC index no) 006-081-00-9	<1	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Ethanol	(CAS No) 64-17-5 (EC no) 200-578-6	(C >= 50) Eye Irrit. 2, H319
	(EC index no) 603-002-00-5	

Full text of H-phrases: see section 16

### **SECTION 4: First aid measures**

#### **Description of first aid measures**

First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. If you feel

unwell, seek medical advice.

Remove all contaminated clothing and footwear. Rinse immediately with plenty of water. If case First-aid measures after skin contact

of redness or irritation, call a doctor.

: Immediately rinse with water for a prolonged period while holding the eyelids wide open. If First-aid measures after eye contact

irritation persists, consult an eye specialist.

First-aid measures after ingestion : Rinse mouth out with water. Get medical advice/attention.

#### Most important symptoms and effects, both acute and delayed

: Headache. Nausea. Vomiting. Giddiness. Loss of coordination. CNS depression. Disturbances Symptoms/injuries

of consciousness. Convulsions. Coma.

Symptoms/injuries after skin contact : Irritation. : Irritation. Symptoms/injuries after eye contact

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

17/06/2015 EN (English) 2/8

### Safety Data Sheet

according to Regulation (EU) No. 2015/830

#### SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2). Powder.

Unsuitable extinguishing media : Water spray.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard Pressurized con

: Pressurized container. On heating there is a risk of bursting due to internal pressure build-up. Toxic vapours may be released. Vapour mixes readily with air, forming explosive mixtures. Heavier than air, vapours may travel long distances along ground, ignite and flash back to

source.

#### 5.3. Advice for firefighters

Firefighting instructions : Clear the danger area. Do not breathe fumes. Cool down the containers exposed to heat with a

water spray. Do not dispose of fire-fighting water in the environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency personnel

Emergency procedures : Avoid contact with skin and eyes. Do not breathe aerosol. Keep away from ignition sources

(including static discharges). In case of important spillage: Only qualified personnel equipped with suitable protective equipment may intervene. Mechanically ventilate the spillage area,

whilst avoiding the formation of explosive concentrations.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Do not discharge into drains (explosive hazard).

### 6.3. Methods and material for containment and cleaning up

For containment : Collect the residue by means of a non-combustible absorbent material.

Methods for cleaning up : Wash contaminated area with large amounts of water.

Other information : Dispose of contaminated materials in accordance with current regulations.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid any direct contact with the product. Do not

breathe spray. Smoking is forbidden. No flames, no sparks. Eliminate all sources of ignition. Access forbidden to unauthorised personnel. Use non-sparking tools. Material and equipment suitable for use under explosive conditions. Avoid high temperatures. Avoid the build-up of electrostatic charge. Do not spray on a naked flame or any incandescent material. Following

use, do not pierce or burn the packaging, even if it is empty.

Hygiene measures : Do not drink, eat or smoke in the workplace. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a cool, well-ventilated place. Keep away from heat. Keep away from sources of

ignition. Protect from sunlight.

Incompatible products : Strong oxidizing agents. Strong bases. Oxidizing materials.

Incompatible materials : Rubbers. Some plastics.

Storage temperature : < 30 °C

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

butanone (78-93-3)		
EU	Local name	Butanone
EU	IOELV TWA (mg/m³)	600 mg/m³
EU	IOELV TWA (ppm)	200 ppm
EU	IOELV STEL (mg/m³)	900 mg/m³
EU	IOELV STEL (ppm)	300 ppm

17/06/2015 EN (English) 3/8

### Safety Data Sheet

according to Regulation (EU) No. 2015/830

butanone (78-93-3)		
United Kingdom	Local name	Butan-2-one
United Kingdom	WEL TWA (mg/m³)	600 mg/m³
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (mg/m³)	899 mg/m³
United Kingdom	WEL STEL (ppm)	300 ppm
United Kingdom	Remark (WEL)	Sk, BMGV
Ethanol (64-17-5)		
United Kingdom	Local name	Ethanol
United Kingdom	WEL TWA (mg/m³)	1920 mg/m³
United Kingdom	WEL TWA (ppm)	1000 ppm
Naphtha (petroleum) hydrotr	eated light (64742-49-0)	
EU	IOELV TWA (mg/m³)	1500 mg/m³
EU	IOELV STEL (mg/m³)	1000 mg/m <sup>3</sup>
dimethyl ether (115-10-6)		
EU	Local name	Dimethylether
EU	IOELV TWA (mg/m³)	1920 mg/m³
EU	IOELV TWA (ppm)	1000 ppm
United Kingdom	Local name	Dimethyl ether
United Kingdom	WEL TWA (mg/m³)	766 mg/m³
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m³)	958 mg/m³
United Kingdom	WEL STEL (ppm)	500 ppm
Butane (106-97-8)		
United Kingdom	Local name	Butane
United Kingdom	WEL TWA (mg/m³)	1450 mg/m³
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m³)	1810 mg/m³
United Kingdom	WEL STEL (ppm)	750 ppm
United Kingdom	Remark (WEL)	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Extraction to remove vapours at their source.

Hand protection : Antistatic gloves. The protective gloves to be used must comply with the specifications of EC

directive 89/686/EEC and the resultant standard EN 374. Breakthrough time: refer to the

recommendations of the supplier

Eye protection : Safety glasses
Skin and body protection : Antistatic clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Aerosol.
Colour : light yellow.
Odour : Solvent.

Odour threshold : No data available pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available Freezing point : No data available

Boiling point : < 0 °C

Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available

Flammability (solid, gas) : Extremely flammable aerosol

Vapour pressure : No data available

17/06/2015 EN (English) 4/8

### Safety Data Sheet

according to Regulation (EU) No. 2015/830

Relative vapour density at 20 °C : > 1

Relative density : 0,636 (liquid) Solubility : Water: Insoluble Log Pow : No data available : No data available Viscosity, kinematic No data available Viscosity, dynamic Explosive properties : No data available : No data available Oxidising properties Explosive limits : No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

To our knowledge, the product does not present any particular risk. Can form explosive peroxides by prolonged contact with air.

### 10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

#### 10.3. Possibility of hazardous reactions

May explode or ignite: on contact with hot surfaces and flames.

#### 10.4. Conditions to avoid

Explosive vapour/air mixtures may be formed. Avoid the build-up of electrostatic charge. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Strong oxidizing agents. Acids. Strong bases. Oxidizing materials.

### 10.6. Hazardous decomposition products

On combustion or on thermal decomposition (pyrolysis) releases : Carbon oxydes (CO, CO2). Hydrogen chloride. Chlorine. Various hydrocarbon fragments.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

Ethanol (64-17-5)		
LD50 oral rat	10470 mg/kg (OECD 401 method)	
LD50 dermal rabbit	> 2000 mg/kg (OECD 402 method)	
LC50 inhalation rat	117 - 125 mg/l/4h (equivalent or similar to OECD Guideline 403)	
Naphtha (petroleum) hydrotreated light (64742	2-49-0)	
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat	> 5 mg/l/4h	
dimethyl ether (115-10-6)		
LC50 inhalation rat (ppm)	164000 ppm/4h	
Butane (106-97-8)		
LC50 inhalation rat	658 mg/l/4h	
Skin corrosion/irritation	Causes skin irritation.	

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated : Not classified (Based on available data, the classification criteria are not met) exposure)

exposure)

Aspiration hazard : Not classified (Technical impossibility to obtain the data)

### **SECTION 12: Ecological information**

## 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

17/06/2015 EN (English) 5/8

## Safety Data Sheet

according to Regulation (EU) No. 2015/830

butanone (78-93-3)	
LC50 fish	2993 mg/l/96h
EC50 Daphnia	308 mg/l/48h
ErC50 (algae)	1972 mg/l/72h
Ethanol (64-17-5)	
LC50 fish	13500 - 15300 mg/l/96h (Pimephales promelas)
EC50 Daphnia	12340 mg/l/48h (Daphnia magna)
ErC50 (algae)	275 mg/l/72h (Chlorella vulgaris)
NOEC (chronic)	> 10 mg/l/ 21 d (Daphnia magna)
NOEC chronic algae	3240 mg/l (Skeletonema costatum)
dimethyl ether (115-10-6)	
LC50 fish	> 4100 mg/l/96h
EC50 Daphnia	> 4400 mg/l/48h (Daphnia magna)
NOEC (acute)	> 4100 mg/l/96h (Poecilia reticulata)

### 12.2. Persistence and degradability

dimethyl ether (115-10-6)	
Persistence and degradability	Not readily biodegradable. (OECD 301D method).

### 12.3. Bioaccumulative potential

dimethyl ether (115-10-6)	
Log Pow	0,18

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

Component	
Ethanol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
	This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of in accordance with relevant local regulations.

Additional information : Following use, do not pierce or burn the packaging, even if it is empty. Empty the packaging

completely prior to disposal. Destroy at an authorised site.

## **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA
14.1. UN number		
1950	1950	1950
14.2. UN proper shipping name		
AEROSOLS	AEROSOLS	Aerosols, flammable
Transport document description		
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	
14.3. Transport hazard class(es)		
2.1	2.1	2.1
	**************************************	***************************************
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes

17/06/2015 EN (English) 6/8

### Safety Data Sheet

according to Regulation (EU) No. 2015/830

#### Special precautions for user 14.6.

### - Overland transport

: 5F Classification code (ADR)

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11 Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP02 : PP87, RR6, L2 Special packing provisions (ADR)

Mixed packing provisions (ADR) : MP9 Transport category (ADR) : 2 Special provisions for carriage - Packages : V14

(ADR)

Special provisions for carriage - Loading,

unloading and handling (ADR)

: CV9, CV12

: S2

Special provisions for carriage - Operation

(ADR)

Tunnel restriction code (ADR) : D

#### - Transport by sea

: 63, 190, 277, 327, 344, 959 Special provisions (IMDG)

Limited quantities (IMDG) : SP277 Excepted quantities (IMDG) : E0 : P207, LP02 Packing instructions (IMDG) : PP87, L2 Special packing provisions (IMDG) : F-D EmS-No. (Fire)

EmS-No. (Spillage) : S-U Stowage category (IMDG) : None MFAG-No : 126

### - Air transport

PCA Excepted quantities (IATA) : E0 PCA Limited quantities (IATA) : Y203 PCA limited quantity max net quantity (IATA) : 30kgG PCA packing instructions (IATA) : 203 PCA max net quantity (IATA) : 75kg CAO packing instructions (IATA) : 203 CAO max net quantity (IATA) : 150kg Special provisions (IATA) : A145, A167 : 10L ERG code (IATA)

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# **SECTION 15: Regulatory information**

#### Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1.

#### 15.1.1. **EU-Regulations**

Contains no substances with Annex XVII restrictions Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances

#### 15.1.2. **National regulations**

No additional information available

### **Chemical safety assessment**

No chemical safety assessment has been carried out

### **SECTION 16: Other information**

Indication of changes:

This sheet was updated (refer to the date at the top of this page). This sheet has been revised completely (changes were not marked).

17/06/2015 EN (English) 7/8

# Safety Data Sheet

according to Regulation (EU) No. 2015/830

Data sources

: ECHA - European Chemical Agency. RTECS (Registry of Toxic Effects of Chemical Substances). TOXNET (Toxicology Data Network) (United States National Library of Medicine).

### Full text of H- and EUH-statements:

Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
EUH208	Contains . May produce an allergic reaction

#### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification and procedure accase delive the classification for mixtures according to regulation (20) 12/2/2000 [CE1].		
Aerosol 1	H222;H229	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 2	H411	Calculation method

### SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

17/06/2015 EN (English) 8/8