



SAFETY DATA SHEET

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : **AlbaChem® Dri-Web Foam Adhesive Spray**
Product code : 1075

Version 1.0 Revision Date 01/03/2024

Manufacturer or supplier's details

Company : **ALBATROSS USA INC./EXPERT WORLDWIDE**

Address : 36-41 36th Street 5439 San Fernando Road West
Long Island City, New York Los Angeles, California
United States United States
11106 90039

Telephone : 718-392-6272 818-543-5850

Emergency Telephone #: Spill, leak, fire, exposure or accident – Call CHEMTREC – Day or Night
1-800-424-9300 or 1-703-527-3887 (USA & Canada)

01-800-681-9531 (México) +56-225814934 (Chile)
01800 -710 -2151 (Colombia) +506-40003869 (Costa Rica)
+507-8322475 (Panamá) +51-17071295 (Perú)

This Safety Data Sheet conforms to the requirements of ANSI Z400.5, and to the format requirements of the Global Harmonizing System. This SDS complies with 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD).

IMPORTANT: Read this SDS before handling and disposing of this product. Pass this information on to employees, customers, and users of this product.

Recommended use : Accelerator
Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a compressed gas
Color	Not applicable
Odor	characteristic

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Compressed gas
Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitization : Category 1
Specific target organ toxicity - : Category 3 (Central nervous system)
single exposure
Specific target organ toxicity - : Category 2
repeated exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements:

H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

Prevention: P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P260 Do not breathe dusts or mists. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection.

Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse.

Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects**Carcinogenicity:**

IARC	No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
propane	74-98-6	30 - 50
acetone	67-64-1	20 - 30
butane	106-97-8	5 - 10
methyl acetate	79-20-9	5 - 10
n-hexane	110-54-3	5 - 10
Hexane, branched and linear	92112-69-1	1 - 5
methylcyclopentane	96-37-7	1 - 5
methanol	67-56-1	0.1 - 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Show this material safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

	Keep patient warm and at rest. Consult a physician after significant exposure.
In case of skin contact	: Wash off immediately with soap and plenty of water. Call a physician if irritation develops or persists.
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids. Seek medical advice.
If swallowed	: If swallowed, call a poison control center or doctor immediately. Do not induce vomiting without medical advice.
Most important symptoms and effects, both acute and delayed	: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO ₂) Sand Foam
Unsuitable extinguishing media	: Water
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	:
Further information	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for fire-fighters	: Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation.
Environmental precautions	: Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.
Methods and materials for containment and cleaning up	: Ventilate the area. Soak up with inert absorbent material. Shovel or sweep up.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation	: Use only with adequate ventilation.
Advice on safe handling	: Wear personal protective equipment. Do not get on skin or clothing. Keep away from heat and flame.

Conditions for safe storage : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Keep in a cool, well-ventilated place.

Materials to avoid : Do not store together with oxidizing and self-igniting products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
propane	74-98-6	TWA	1,000 ppm	ACGIH		
		TWA	1,000 ppm 1,800 mg/m ³	NIOSH REL		
		TWA	1,000 ppm 1,800 mg/m ³	OSHA Z-1		
		TWA	1,000 ppm 1,800 mg/m ³	OSHA P0		
		PEL	1,000 ppm 1,800 mg/m ³	CAL PEL		
		acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH		
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1		
		TWA	750 ppm 1,800 mg/m ³	OSHA P0		
		STEL	1,000 ppm 2,400 mg/m ³	OSHA P0		
		STEL	750 ppm 1,780 mg/m ³	CAL PEL		
		C	3,000 ppm	CAL PEL		
		PEL	500 ppm 1,200 mg/m ³	CAL PEL		
butane	106-97-8	TWA	800 ppm 1,900 mg/m ³	OSHA P0		
		TWA	1,000 ppm	ACGIH		
		TWA	1,000 ppm	ACGIH		
		PEL	800 ppm 1,900 mg/m ³	CAL PEL		
		STEL	1,000 ppm	ACGIH		
methyl acetate	79-20-9	TWA	200 ppm	ACGIH		
		STEL	250 ppm	ACGIH		
		TWA	200 ppm 610 mg/m ³	OSHA Z-1		
		TWA	200 ppm 610 mg/m ³	OSHA P0		
		STEL	250 ppm 760 mg/m ³	OSHA P0		
		PEL	200 ppm 610 mg/m ³	CAL PEL		
		STEL	250 ppm 760 mg/m ³	CAL PEL		
		n-hexane	110-54-3	TWA	50 ppm	ACGIH
				TWA	500 ppm 1,800 mg/m ³	OSHA Z-1

		TWA	50 ppm 180 mg/m ³	OSHA P0
		PEL	50 ppm 180 mg/m ³	CAL PEL
Hexane, branched and linear	92112-69-1	TWA	500 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
		TWA	500 ppm 1,800 mg/m ³	OSHA P0
		STEL	1,000 ppm 3,600 mg/m ³	OSHA P0
		TWA	100 ppm 350 mg/m ³	NIOSH REL
		C	510 ppm 1,800 mg/m ³	NIOSH REL
		PEL	500 ppm 1,800 mg/m ³	CAL PEL
		STEL	1,000 ppm 3,600 mg/m ³	CAL PEL
methylcyclopentane	96-37-7	TWA	500 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
		TWA	500 ppm 1,800 mg/m ³	OSHA P0
		STEL	1,000 ppm 3,600 mg/m ³	OSHA P0
methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m ³	OSHA Z-1
		STEL	250 ppm 325 mg/m ³	OSHA P0
		TWA	200 ppm 260 mg/m ³	OSHA P0
		C	1,000 ppm	CAL PEL
		PEL	200 ppm 260 mg/m ³	CAL PEL
		STEL	250 ppm 325 mg/m ³	CAL PEL

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Combined particulates and organic vapor type
- Hand protection
Material : Nitrile rubber
- Eye protection : Tightly fitting safety goggles
Ensure that eyewash stations and safety showers are close to the workstation location.
- Skin and body protection : Long sleeved clothing
Preventive skin protection
- Protective measures : Avoid contact with skin.
- Hygiene measures : Avoid contact with skin, eyes and clothing.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a compressed gas
Color	: Not applicable
Odor	: characteristic
Odor Threshold	: no data available
pH	: is not determined
Melting point/freezing point	: is not determined

Boiling point/boiling range	: is not determined
Flash point	: -104.4 °C Method: closed cup Not applicable
Evaporation rate	: is not determined
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: Upper flammability limit is not determined
Lower explosion limit	: Lower flammability limit is not determined
Vapor pressure	: is not determined
Density	: 0.7112 g/cm ³ (20 °C)
Solubility(ies)	
Water solubility	: is not determined
Partition coefficient: n- octanol/water	: no data available
Autoignition temperature	: is not determined
Viscosity	
Viscosity, kinematic	: is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: The product is chemically stable.
Hazardous decomposition products	: Nitrogen oxides (NO _x) Sulfur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : > 200 mg/l Exposure time: 4 Hours Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

methyl acetate:

Acute inhalation toxicity : LC50 Rat: 16000 ppm
Exposure time: 4 h
Test atmosphere: vapor

n-hexane:

Acute dermal toxicity : LD50 Dermal Rabbit: 3,000 mg/kg

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Product:

Germ cell mutagenicity-
Assessment : Tests on bacterial or mammalian cell cultures did not show
mutagenic effects.

Carcinogenicity

Product:

Carcinogenicity -
Assessment : Not classifiable as a human carcinogen

Reproductive toxicity

Product:

Reproductive toxicity -
Assessment : No toxicity to reproduction

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

methyl acetate :

Toxicity to fish

: LC50 (Brachydanio rerio (zebrafish)): 250 - 350 mg/l
Exposure time: 96 h
Test Method: static test

n-hexane :

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.1 - 2.98 mg/l
Exposure time: 96 h
Test Method: flow-through test

Persistence and degradability

No data available

Bioaccumulative potential

Components:

acetone :

Partition coefficient: n-octanol/water : log Pow: -0.24

methyl acetate :

Partition coefficient: n-octanol/water : log Pow: 0.18

n-hexane :

Partition coefficient: n-octanol/water : log Pow: 3.90

methylcyclopentane :

Partition coefficient: n-octanol/water : log Pow: 3.37

methanol :

Partition coefficient: n-octanol/water : log Pow: -0.77

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of together with household waste.
Do not dispose of waste into sewer.
To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended, as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203

Packing instruction (passenger aircraft) : 203
IMDG-Code
UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1950
Proper shipping name : Aerosols

Class : 2.1
Packing group : Not assigned by regulation
Labels : FLAMMABLE GAS
ERG Code : 126
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure
Respiratory or skin sensitization
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

n-hexane	110-54-3
----------	----------

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

n-hexane	110-54-3
methanol	67-56-1

US State Regulations

California Prop 65 Please contact Supplier for more information.

The ingredients of this product are reported in the following inventories:

TSCA	All substances listed as active on the TSCA inventory
AIIC	On the inventory, or in compliance with the inventory
DSL	All components of this product are on the Canadian DSL
KECI	On the inventory, or in compliance with the inventory
PICCS	On the inventory, or in compliance with the inventory
IECSC	On the inventory, or in compliance with the inventory


Inventories Legend TSCA (USA), DSL (Canada), REACH(Europe), AIIC (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Office - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

Further information

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	4
PHYSICAL HAZARD	3

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.